YOUR PICNIC TABLE HAS BEEN PARTIALLY ASSEMBLED FOR YOU.

Just follow the steps below to finish assembling.

<u>STEP 1:</u> PLACE PICNIC TABLE LEGS UPRIGHT ON FLAT SURFACE, MAKING SURE THE <u>PILOT HOLES</u> NEAR THE TOP OF THE TABLE LEGS ARE FACING OUTWARD.

STEP 2: PLACE SEAT ASSEMBLIES ONTO THE LEGS, MAKING SURE THE FRAMEWORK FITS INTO THE SLOTS IN THE TABLE LEGS AND THE LEGS ARE ON THE INSIDE OF THE ANGLE IRON SUPPORTS ON THE FRAME. LINE UP THE HOLES IN THE FRAMEWORK WITH THE HOLES IN THE LEGS. FASTEN LEGS TO FRAMEWORK USING 2 OF THE 2" LAG SCREWS AND 2 FLAT WASHERS PER SEAT ASSEMBLY END. DO NOT TIGHTEN!!

STEP 3: PLACE THE TABLE TOP ASSEMBLY ONTO THE LEGS SO THE FRAMEWORK FITS INTO THE SLOTS ON EACH

ASSEMBLY INSTRUCTIONS 6' WALK THRU PICNIC TABLE

REF#	QTY	DESCRIPTION
1	1	TABLE TOP (Assembled)
2	2	TABLE SEAT (Assembled)
3	2	PLASTIC TABLE LEGS
4	2	27-1/4" DIAGONAL TABLE BRACES
		HARDWARE KIT
5	18	3/8" x 2" LAG SCREW
6	19	3/8" FLAT WASHER
7	1	3/8" x 1-1/4" HEX HEAD CAP SCREW
8	1	3/8" FLANGE NUT

TABLE LEG AND THE LEGS ARE ON THE <u>INSIDE</u> OF THE ANGLE IRON SUPPORTS ON THE FRAME. FASTEN THE TABLE TOP ASSEMBLY TO THE LEGS USING 4 OF THE 2" LAG SCREWS AND 4 FLAT WASHERS PER END. **DO NOT TIGHTEN!!**

STEP 4: INSTALL DIAGONAL TABLE BRACES UNDERSIDE OF THE TABLE TOP ASSEMBLY USING THE 1-1/4" HEX HEAD CAP SCREW, 1 FLAT WASHER AND 1 FLANGE NUT. LOOSELY TIGHTEN THE NUT. ATTACH THE BRACES TO THE LEGS USING 1 OF THE FLAT WASHERS AND 1 OF THE 2" LAG SCREWS PER SIDE. ONCE ALL BRACES ARE LOOSELY ATTACHED, SQUARE UP THE PICNIC TABLE LEGS WITH THE TOP AND SEATS TIGHTEN LAG SCREWS TO THE LEGS FIRST, THEN TIGHTEN THE CENTER BRACE.

STEP 5: TIGHTEN ALL FASTNERS.

